



PROCHAMPION 2500 A With high-flow watering spray line and road sign kit



PROCHAMPION 2500 A With high-flow watering spray line and road sign kit



PROCHAMPION 2500 A with telescopic mixed hitch



Rabaud
advantages

- Large sweeping widths: 2 m or 2.50 m.
- Adaptation on front 3-point linkage or on telescopic.
- Robust frame for intensive work
- 1 or 2 hydraulic motor(s) depending on the carrier oil flow (120 L/min. max.).
- Floating coupling to follow road form thanks to the swiveling system
- 30° mechanically swivelling hitch (hydraulic in option).
- +/- 420 mm mechanical offset (hydraulic in option) separate from angling
- Hydraulic engine integrated in the metal hub of the brush to save room and for more protection.
- Wide brush with polyester fibre for better lasting (inner size: Ø 178 mm / outer size: Ø 600 mm).
- 2 height-adjustable, swivelling puncture-proof wheels (Ø 250 mm).
- Pressure watering option to connect directly to your tank.

Technical characteristics

MODELS	PROCHAMPION 2000 A	PROCHAMPION 2500 A
<i>Brush length</i>	1980 mm	2460 mm
<i>Brush diameter (inner / outer)</i>	178 mm / 600 mm	
<i>Hub</i>	Metal	
<i>Brush fibre type</i>	Polyester	
<i>Offset</i>	420 mm right & left (only on tractor)	
<i>Angling</i>	+/- 30°	
<i>Oscillation</i>	On floating coupling	
<i>Dimensions (L x W x H)</i>	1,67 x 2,09 x 1,26 m	1,67 x 2,55 x 1,26 m
<i>Weight (without option)</i>	640 kg	660 kg
<i>Coupling</i>	No. 2 front 3-point hitch with removable bar	
<i>Flow 1 hydraulic motor</i>	30 L/min. mini. - 60 L/min. max.	
<i>Flow 2 hydraulic motor</i>	61 L/min. mini. - 120 L/min. max.	

Standard equipment

- Anti-projection guard.
- 3-point linkage with oscillating top link.
- 2 control tyre wheels (diameter 250 mm), swiveling and adjustable in height.
- Brush rings with extra long polyester fibre for longer lifespan.
- Mechanical angling +/- 30°.
- Mechanical offset +/- 420 mm (only on tractor).
- 2 hydraulic hoses with 2 ½" male valve couplings.



PROCHAMPION on tractor front 3-point linkage

				£ Reference		£ Reference	
MODELS				PROCHAMPION 2000 A		PROCHAMPION 2500 A	
PROCHAMPION for tractor with 1 hydraulic motor (for carrier with oil flow < 60 L/min.) • Without hydraulic valves - With polyester brush				7,065	72083E	7,455	72082E
PROCHAMPION for tractor with 2 hydraulic motor (for carrier with oil flow > 60 L/min.) • Without hydraulic valves - With polyester brush				7,730	72085E	8,375	72084E
OPTIONS							
Hydraulic offset				785	72032E	785	72032E
Hydraulic orientation				865	72086E	865	72086E
High pressure watering line with 4 sprayers (without water tank)				405	72064E	405	72064E
Scrape blade				-		2,910	72061J
12 V worksite signs kit with retroreflective tape, 2 lumifog... (requires power supply)				340	72095C	340	72095C
Linkage n°3 with swinging drawbar				225	72071E	225	72071E
Mixed hitch for second carrier like a telescopic				1,060	72064F	1,060	72064F
180 bar pressure limiter (for sweeper with only 1 motor)				220	72022J	220	72022J
Hydraulic valve	6-way valve with electric extension 5 m long			775	72035G	775	72035G
	8-way valve with electric extension 5 m long			945	72036G	945	72036G
Specific painting				165	72009C	165	72009C
EPOXY painting				385	72033G	385	72033G
Electro-hydraulic control with radio-control	Sweeper with 1 hydraulic motor	2-way valve dual-acting		2,565	72066E	2,565	72066E
		3-way valve dual-acting		2,970	72067E	2,970	72067E
	Sweeper with 2 hydraulic motor	2-way valve dual-acting		3,360	72069E	3,360	72069E
		3-way valve dual-acting		3,685	72070E	3,685	72070E
SPARE BRUSH							
Polyester brush ring Ø 600 mm, value for 1 m				420	24F004	420	24F004

✓ OPTIONS



Linkage n°3 with swinging drawbar



Mixed hitch for second carrier like a telescopic



High pressure watering line, 4 sprayers



Hydraulic angling



Hydraulic offsetting



Scrape blade